

Guangzhou YuBen Hydraulic Technology Co., Ltd

Add: A5 Factory, Lanyuan Industrial Zone, No. 8 Xinwu Sixth Street, Zhaidong Village, Yongning Street, Zengcheng District, Guangzhou









YUBEN NC machine provide fast and accurate crimping for fitting manufacturing. Crimping range is 12-49 mm.





TECHNICAL DATA	
Max crimping dia (mm)	12-49
Max crimping dia (inches)	0.47-1.93
Max. crimping force (kN)	500
Max. crimping force (tonnage)	50
Cycle time 10 mm (s) Tri/Mono	1.5
Hose size ID (inches)	11/4
Dies set series	NC20
Max. opening (mm)	+18
Max.opening without dies (mm)	117
Master die D / L (mm)	99/22
Master die D / L (inches)	3.90/0.87
Motor Tri/Mono (kW/HP)	3.0/4.0
Oil tank volume (L)	50
Motor Voltage(V): Tri	200/220/380/440
Motor Voltage(V): Mono	220/230/240

NC 20 Die:			
DieSetNo	Crimping range	ID (mm)	L (mm)
NC20/12	12.0-16.0	12	3
NC20/16	16.0-22.0	16	4
NC20/22	22.0-26.0	22	4.5
NC20/26	26.0-34.0	26	5
NC20/34	34.0-39.0	34	5
NC20/39	39.0-49.0	39	5

DIMENSIONS (L x W x H)		
Machine (mm)	820X750X1030	
Machine (inch)	32.3X29.5X40.6	
Package (mm)	925X925X1220	
Package (inch)	36.4X36.4X48.0	

WEIGHT (KG)	
N, W.	287
G.W.	317