



YB-NC30h FEATURES



YUBEN NC machine provide fast and accurate crimping for fitting manufacturing. Crimping range is 10-93 mm.



TECHNICAL DATA

Max crimping dia (mm)	10-93
Max crimping dia (inches)	0.47-2.48
Max. crimping force (kN)	850
Max. crimping force (tonnage)	85
Cycle time 10 mm (s) Tri/Mono	1.4
Hose size ID (inches)	2
Dies set series	NC20/NC30
Max. opening (mm)	+26
Max. opening without dies (mm)	140
Master die D / L (mm)	134/33
Master die D / L (inches)	3.90/1.38
Motor Tri/Mono (kW/HP)	3/5.5
Oil tank volume (L)	50
Motor Voltage (V): Tri	200/220/380/440
Motor Voltage (V): Mono	220/230/240

DIMENSIONS (L x W x H)

Machine (mm)	820X750X1030
Machine (inch)	32.3X29.5X40.6
Package (mm)	925X925X1220
Package (inch)	36.4X36.4X48.0

CONTROL

- ※Semi-Automatic
- ※Automatic
- ※CNC

NC30 Dies:

DieSetNo	Crimping range	ID (mm)	L (mm)
NC30/10	10.0-12.0	10	3
NC30/12	12.0-14.0	12	3
NC30/14	14.0-16.0	14	3
NC30/16	16.0-19.0	16	4
NC30/19	19.0-22.0	19	4
NC30/22	22.0-26.0	22	4.5
NC30/26	26.0-30.0	26	4.5
NC30/30	30.0-34.0	30	5
NC30/34	34.0-39.0	34	5
NC30/39	39.0-45.0	39	5
NC30/45	45.0-51.0	45	5
NC30/51	51.0-57.0	51	5
NC30/57	57.0-63.0	57	5
NC30/63*	63.0-69.0	63	5
NC30/69*	69.0- 73.0	69	5
NC30/73*	73.0-81.0	73	6
NC30/81*	81.0-93.0	81	7

*: Non standard die